

## 355 Collare con sgancio, dado puntato

Collar for pipe clamping-spot welded nut  
Schellen für Rohrbefestigung-punktgeschweisste Mutter  
Collier de fixation pour tube-ecrou soude par points  
Abrazadera fijacion tubo-tuerca soldada por puntos

Nota: dado saldato a punti (a resistenza)

Sgancio brevettato **PRATIKO**®

Materiale: St. W 24



vite



tassello



## 351 Collare con sgancio senza vite e tassello, dado puntato

Collar for pipe clamping without dowel & wood-iron screw  
Schellen für Rohrbefestigung ohne Dubel und Eisen-Holzschraube  
Collier de fixation pour tube sans cheville et vis fer-bois  
Abrazadera fijacion tubo sin taco ni tornillo


Nota: dado saldato a punti (a resistenza)

Sgancio brevettato **PRATIKO**®

Materiale: St. W 24

Codice con Vite + tassello	Codice senza Vite + tassello	DN inch	ø interno mm	Fascia lg x sp mm	Vite con canalina mm	Vite mm	Tassello mm
355308000	351308000	3/8"	16-18	20 x 2,5	M 6 x 20	M 8 X 90	10 x 70
355102000	351102000	1/2"	20-22	20 x 2,5	M 6 x 20	M 8 X 90	10 x 70
355304000	351304000	3/4"	25-28	20 x 2,5	M 6 x 20	M 8 X 90	10 x 70
355100000	351100000	1"	31-34	20 x 2,5	M 6 x 25	M 8 X 90	10 x 70
355114000	351114000	1" 1/4	39-43	20 x 2,5	M 6 x 25	M 8 X 90	10 x 70
355112000	351112000	1" 1/2	45-48,5	20 x 2,5	M 6 x 25	M 8 X 90	10 x 70
355200000	351200000	2"	58-61	20 x 2,5	M 6 x 25	M 8 X 90	10 x 70
355212000	351212000	2" 1/2	73-76,5	30 x 2,5	M 6 x 25	M 10 x 120	14 x 70
355300000	351300000	3"	86-89	30 x 2,5	M 6 x 25	M 10 x 120	14 x 70
355400000	351400000	4"	110-115	30 x 2,5	M 6 x 25	M 10 x 120	14 x 70

Vite ferro-legno: M 8 x 90 mm cod. 216008090 - M 10 x 120 mm cod. 216010120 Tassello: 10 x 70 mm cod. 252100700 - 14 x 70 mm cod. 252140700



## 355/G Collari con sgancio, dado puntato e rivestimento in gomma


Collar for pipe clamping-spot welded nut with rubber gasket  
Schellen für Rohrbefestigung punktgeschweisste Mutter mit Gummieinlage  
Collier de fixation pour tube-ecrou soude par points garniture isophonique  
Abrazadera fijacion tubo-tuerca soldada-junta de goma

Nota: dado saldato a punti (a resistenza)

Sgancio brevettato **PRATIKO**®

Materiale: St. W 24

Gomma vulcanizzata: EPDM nera durezza 55 Shore (-20° C/+120° C)



## 351/G Collare con sgancio, rivestimento in gomma senza vite e tassello, dado puntato

Collar for pipe clamping with rubber gasket without dowel & wood-iron screw  
Schellen für Rohrbefestigung mit Gummieinlage ohne Dubel und Eisen-Holzschraube  
Collier de fixation garniture isophonique sans cheville et vis fer-bois  
Abrazadera fijacion junta de goma sin taco ni tornillo

Nota: dado saldato a punti (a resistenza)

Sgancio brevettato **PRATIKO**®

Materiale: St. W 24

Gomma vulcanizzata: EPDM nera durezza 55 Shore (-20° C/+120° C)

Conforme a  
Conform to  
Entsprechend  
Correspondant  
Conforme a la

**DIN 4109**

Codice con Vite + tassello	Codice senza Vite + tassello	DN inch	ø interno mm	Fascia lg x sp mm	Vite con canalina mm	Vite mm	Tassello mm
355150001	351150001	ø 15	15-18	20 x 2,5	M 6 x 20	M 8 X 90	10 x 70
355308001	351308001	3/8"	17-19	20 x 2,5	M 6 x 20	M 8 X 90	10 x 70
355102001	351102001	1/2"	21-23	20 x 2,5	M 6 x 20	M 8 X 90	10 x 70
355304001	351304001	3/4"	26,5-28	20 x 2,5	M 6 x 20	M 8 X 90	10 x 70
355100001	351100001	1"	33-35	20 x 2,5	M 6 x 25	M 8 X 90	10 x 70
355114001	351114001	1" 1/4	42-45	20 x 2,5	M 6 x 25	M 8 X 90	10 x 70
355112001	351112001	1" 1/2	48-50	20 x 2,5	M 6 x 25	M 8 X 90	10 x 70
355200001	351200001	2"	60-64	20 x 2,5	M 6 x 25	M 8 X 90	10 x 70
355212001	351212001	2" 1/2	71-80	30 x 2,5	M 6 x 25	M 10 x 120	14 x 70
355300001	351300001	3"	81-89	30 x 2,5	M 6 x 25	M 10 x 120	14 x 70
355312001	351312001	3" 1/2	99-103	30 x 2,5	M 6 x 25	M 10 x 120	14 x 70
355400001	351400001	4"	108-116	30 x 2,5	M 6 x 25	M 10 x 120	14 x 70

Vite ferro-legno: M 8 x 90 mm cod. 216008090 - M 10 x 120 mm cod. 216010120 Tassello: 10 x 70 mm cod. 252100700 - 14 x 70 mm cod. 252140700